

**COAXIAL FIXED ATTENUATOR, 50 Ohm, 30 dB, N**

6830.17.A

**Properties**

- Wide range of interfaces
- Fixed attenuation level from 0 dB up to 40 dB
- 50  $\Omega$  or 75  $\Omega$  impedance
- Various bandwidth to improve the impedance matching between subsystems of its waveform
- Used in many test and measurement and communication applications.



Product configuration		
Interface	Gender	Standard
N	plug (male)	IEC 60169-16_MIL-STD-348A/304_CECC 22210
N	jack (female)	IEC 60169-16_MIL-STD-348A/304_CECC 22210

Electrical data	
Impedance	50 $\Omega$
Operating frequency	0 GHz ... 12.4 GHz
Attenuation nominal	30 dB
VSWR	1.25
Return loss	19.1 dB

Electrical Data (frequency related)		
Frequency range	Attenuation deviation	VSWR max
0 GHz to 4 GHz	+/- 1 dB	1.1
4 GHz to 8 GHz	+/- 1 dB	1.2
8 GHz to 10 GHz	+/- 1 dB	1.2
10 GHz to 12.4 GHz	+/- 1 dB	1.25

**COAXIAL FIXED ATTENUATOR, 50 Ohm, 30 dB, N**

6830.17.A

<b>Electrical Data (power)</b>	
Average power	1 W at 30 °C ambient temperature. Linearly derated to 0 W at 130 °C ambient temperature.
Peak power	500 W, 5 µs pulse width, 0.05 % duty cycle
Electrical remarks	Peak voltage max. 160V (50 Ohm)

<b>Interface and material data</b>		
Interface	N / plug (male)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Brass	Gold Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Interface	N / jack (female)	
<b>Piece parts</b>	<b>Material</b>	<b>Plating</b>
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer conductor	Brass	Gold Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

<b>Environmental data</b>	
Operation temperature	-55 °C ... 130°C

<b>Ordering Information Table</b>	
Item number	Item description
22550187	6830.17.A

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.

DOCUMENT PIM-P1608 / Date of publication: 23.11.2023 / uncontrolled copy